

# MAXIM PLUS<sup>TM</sup>

LABEL SYSTEM

## Ultrashield 25 25% Floor Finish

### Features:

- High Solids - Requires Fewer Coats / Less Labor**
- Durable, Non-Yellowing**
- Excellent Off-the-Mop Gloss**

### Description

Designed for the professional floor crew that needs a finish that will require less coats and still give the high gloss demanded in today's markets. This product uses a special polymer, resin, wax ratio to provide superior initial gloss with unsurpassed durability. As little as 2 coats are needed for most applications. Finish dries to a clear film that will not yellow over time.

### Directions

- 

**1** **Wear safety glasses & gloves**  
*Usar gafas de seguridad y guantes*
- 

**2** **Apply 3 - 5 coats evenly with clean finish mop**  
*Aplique uniformemente 3-5 capas con una mopa de acabado limpia*
- 

**3** **Allow to dry 30 - 45 minutes between coats**  
*Deje secar 30-45 minutos entre una capa y otra*
- 

**4** **Completely dry before applying next coat**  
*Seque completamente antes de aplicar la capa siguiente*
- 

**5** **Allow at least 24 hours before use**  
*Deje pasar al menos 24 horas antes del uso*



### Applications

- For regular stripping / buffing in:**
- > Schools and hospitals
  - > Airports
  - > Offices

### Specifications

Color .....	White
Fragrance .....	Characteristic
pH Range .....	8.0 - 8.5
Dilution .....	RTU
Density .....	8.60
Non-volatile solids .....	25%
Coverage .....	2000 sq. ft. / gal.

### Packaging

4/1 gallon	122500-41
2.5 gallon	122500-07
5 gallon	122500-05
55 gallon	122500-55



FLOOR COATING AND FINISHING MATERIAL  
AS TO SLIP RESISTANCE ONLY  
8P89