

MAXIM PLUSTM

LABEL SYSTEM

High Gloss Floor Finish

Features:

- High Solids - Requires Fewer Coats / Less Labor**
- Hard, Durable, Non-Yellowing**
- Excellent Off-the-Mop Gloss**

Description

A high solids, self sealing floor finish that delivers a consistent high level of appearance over an extended period of time. This is a fast drying, low odor, versatile finish that can be maintained using standard scrub and recoat low maintenance programs while also responding well to frequent high speed burnishing. Up to 5 coats can be applied with as little as 30 minutes drying time between coats depending on conditions.

Directions

- 

1 **Wear safety glasses & gloves**
Usar gafas de seguridad y guantes
- 

2 **Apply 3-5 coats evenly with a clean finish mop**
Aplique 3 - 5 capas de manera uniforme con un trapeador de acabado limpio
- 

3 **Wait 30 - 45 minutes between coats**
Espere de 30 - 45 minutos entre capas
- 

4 **Completely dry before applying next coat**
Seque completamente antes de aplicar la capa siguiente
- 

5 **Let dry completely before allowing traffic**
Dejar secar completamente antes de permitir el tránsito



Applications

- For maintenance in:**
- > Schools and offices
 - > Supermarkets and retail
 - > Hospitals and medical centers

Specifications

| | |
|-----------------|---------------------|
| Color | White |
| Fragrance | Characteristic |
| pH Range | 8.0 - 8.5 |
| Dilution | RTU |
| Density | 8.65 |
| Coverage | 2000 sq. ft. / gal. |

Packaging

| | |
|--------------|-----------|
| 4/1 gallon | 132500-41 |
| 2/2.5 gallon | 132500-07 |
| 5 gallon | 132500-05 |