

MAXIM®

20% Ultra High Speed Floor Finish

Features:

Balances Price with Performance

Durable, Easy to Maintain, Non-Yellowing

Good Off-the-Mop Gloss

Description

This product is designed for supermarkets, retail, and institutional settings on all types of resilient flooring. Gives the ultimate in wet look gloss with superb detergent resistance and durability. Clear, non-yellowing formula resists dirt penetration to stay looking clean longer.

Due to the superior burnish response and repairability, this is the recommended product for floors that will be scrubbed and burnished daily or several times per week.

Directions

For floor finishing:

- 1 Thoroughly strip floor according to stripper label instructions, and allow to dry completely.
- 2 Use a mop or applicator to apply 3 - 7 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Allow a minimum of 2 hours of drying time before burnishing. For best results, allow 24 hours of drying time before burnishing, and use a floor cleaner with a damp mop or auto scrubber with a Red Pad.
- 4 For maintenance, dust mop or damp mop as needed.
- 5 For periodic deep scrub and before recoating, use a floor cleaner with autoscrubber and Blue Pad.

For concrete, terrazzo, marble or granite:

- 1 Apply two coats of floor sealer according to sealer label instructions.
- 2 Use a mop or applicator to apply 3 - 5 coats of finish. Allow 30 - 45 minutes of drying time between coats.
- 3 Burnish, maintain and restore as above.

Recommended pads for buffing or burnishing:

*Americo Combo | ETC Gorilla Lite | Glit Joey | Microtron White Polish
3M White Polish | Triple S White Polish*



Applications

For daily maintenance in:

- > Schools and offices
- > Supermarkets and retail
- > Hospitals and medical centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.60
Non-volatile solids	20%
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	152000-41
5 gallon	152000-05
55 gallon	152000-55