

MAXIM PLUS LABEL SYSTEM

Ultrashield 22 UF 22% Urethane Fortified Floor Finish

Features:

- Balances Price with Performance
- Durable, Easy to Maintain, Non-Yellowing
- Good Off-the-Mop Gloss

Description

This product is designed for heavy traffic areas such as supermarkets, retail, and institutional settings on all types of resilient flooring. Unique water based urethane emulsion gives a superior wet look gloss with superb detergent resistance and durability.

Contains UFW technology to prevent discoloration and dirt penetration to stay looking clean longer, extending the period between stripping cycles.

Directions

- 

1 Wear safety glasses & gloves
Usar gafas de seguridad y guantes
- 

2 Strip floor and apply 3 - 7 coats evenly
Limpie el piso y aplique uniformemente 3 - 7 capas
- 

3 Allow to dry 30 - 45 minutes between coats
Deje secar 30-45 minutos entre una capa y otra
- 

4 Completely dry between coats and allow 24 hours before use
Seque completamente entre una capa y otra, y deje pasar 24 horas antes del uso
- 

5 Do not apply more than 4 coats in a 24-hour period
No aplique más de 4 capas en un período de 24 horas



Applications

- For daily maintenance in:**
- > Schools and offices
 - > Supermarkets and retail
 - > Hospitals and medical centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.60
Non-volatile solids	22%
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	152400-41
5 gallon	152400-05
2/2.5 gallon	152400-07
55 gallon	152400-55

