

MAXIM PLUS LABEL SYSTEM

Ultrashield 28 UF 25% Urethane Fortified Floor Finish

Features:

- High Solids - Requires Fewer Coats / Less Labor
- Durable, Easy to Maintain, Non-Yellowing
- High Off-the-Mop Gloss

Description

The ultimate in appearance and durability, this product gives you maximum protection in fewer coats. Save time and labor dollars while enhancing the beauty of your floors. Maintenance has never been so easy. Perfect for high speed and propane burnishers, this product also maintains its high appearance level even when buffing is not possible. Perfectly clear and non-yellowing, each film coat molecularly bonds together to provide extended durability. This product is easy to apply with mop or applicator.

Directions

- 

1 Wear safety glasses & gloves
Usar gafas de seguridad y guantes
- 

2 Strip floor and apply 3 - 7 coats evenly
Limpie el piso y aplique uniformemente 3 - 7 capas
- 

3 Allow to dry 30 - 45 minutes between coats
Deje secar 30-45 minutos entre una capa y otra
- 

4 Completely dry between coats and allow 24 hours before use
Seque completamente entre una capa y otra, y deje pasar 24 horas antes del uso
- 

5 Do not apply more than 4 coats in a 24-hour period
No aplique más de 4 capas en un período de 24 horas



Applications

For daily maintenance in:

- > Schools and offices
- > Supermarkets and retail
- > Hospitals and medical centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.65
Non-volatile solids	25%
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	152500-41
5 gallon	152500-05
2/2.5 gallon	152500-07
55 gallon	152500-55



FLOOR COATING AND FINISHING MATERIAL
AS TO SLIP RESISTANCE ONLY
8P89