

MAXIM **POUS**

Premium High Solids Floor Finish

Features:

High Solids - Requires Fewer Coats / Less Labor Durable, Easy to Maintain, Non-Yellowing High Off-the-Mop Gloss

Description

A premium ultra high speed floor finish formulated to achieve the highest level of gloss and appearance. Optically enhance polymer provides a very high distinction of image that is non-yellowing, scuff resistant, and very responsive to ultra high speed burnishing.

Directions



Wear safety glasses & gloves Usar gafas de seguridad y quantes

Apply up to 5 coats evenly with a clean finish mop

Aplique hasta 5 capas de manera uniforme con un trapeador de acabado limpio

Wait 30 - 45 minutes between coats Espere de 30 - 45 minutos entre capas

Completely dry before applying next coat Seque completamente antes de aplicar la capa siguiente

Let dry completely before allowing traffic Dejar secar completamente antes de permitir el tránsito



Applications

For daily maintenance in:

- > Schools and offices
- > Supermarkets and retail
- > Hospitals and medical centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	
Dilution	RTU
Density	
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	152500-41
5 gallon	152500-05
2/2.5 gallon	152500-07
55 gallon	152500-55



FLOOR COATING AND FINISHING MA AS TO SLIP RESISTANCE ONL' 8P89



Contact your Account Representative for more information

J40 Private Brand Way, Athens, TN 37303 | 800.467.6294 | fax: 423.337.3369 | midlab.com erything Clean © 2018 Midlab, Inc. All right reserved. PLUS Label System is a trademark of Midlab, Inc. Patent Pending