

MAXIM PLUS LABEL SYSTEM

Ultimate UltraClear™ Fortified Floor Finish

Features:

- High Solids - Requires Fewer Coats / Less Labor
- Durable, Easy to Maintain, Non-Yellowing
- High Off-the-Mop Gloss

Description

This product is a premium, ultra high solids floor finish offering high off-the-mop gloss in as little as 3 coats. Utilizing the latest polymer technology, this product is extremely durable and easy to repair. This product can be maintained using all maintenance programs.

Directions

- 

1 Wear safety glasses & gloves
Usar gafas de seguridad y guantes
- 

2 Strip floor and apply 3 - 7 coats evenly
Limpie el piso y aplique uniformemente 3 - 7 capas
- 

3 Allow to dry 30 - 45 minutes between coats
Deje secar 30-45 minutos entre una capa y otra
- 

4 Completely dry between coats and allow 24 hours before use
Seque completamente entre una capa y otra, y deje pasar 24 horas antes del uso
- 

5 Do not apply more than 4 coats in a 24-hour period
No aplique más de 4 capas en un período de 24 horas



Applications

- For daily maintenance in:**
- > Schools and offices
 - > Supermarkets and retail
 - > Hospitals and medical centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.60
Non-volatile solids	25%
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	157500-41
5 gallon	157500-05
2/2.5 gallon	157500-07
55 gallon	157500-55



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 8P89