

MAXIM PLUSTM

LABEL SYSTEM

Hardcoat

Features:

- Low Odor, Quick Drying**
- Durable, Resists Scuffs and Marks**
- Non-Yellowing, Non-Flammable**

Description

Designed to seal and protect concrete, terrazzo, and other stone surfaces. This formula has excellent resistance to many types of chemicals including greases, oils, and gasoline. An excellent base coat on terrazzo prior to application of floor finish that will help prolong the life of the floor finish.

Directions

- 

Wear safety glasses & gloves
Usar gafas de seguridad y guantes
- 

Apply 1-2 coats evenly with a clean finish mop
Aplique 1 - 2 capas de manera uniforme con un trapeador de acabado limpio
- 

Wait 30 - 45 minutes between coats
Espere de 30 - 45 minutos entre capas
- 

Completely dry before applying next coat
Seque completamente antes de aplicar la capa siguiente
- 

Allow final coat to dry for 6 - 8 hours
Permita que la capa final se seque durante 6 - 8 horas



Applications

For sealing and protecting:

- > Concrete and brick
- > Slate and quarry tile
- > Unglazed ceramic tile

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.59
Coverage	2000 sq. ft. / gal.

Packaging

5 gallon 163000-05