



Sunrise Finish

Features:

Metal-Free

Buffable

Durable

Environmentally Responsible Choice

Description

Nattura® Sunrise Finish is EcoLogo™ Certified to Hard Floor Care Products, UL 2777. This easy-to-apply finish contains no zinc or other heavy metals, contains minimal volatile organic compounds (V.O.C.), and uses environmentally responsible solvents and emulsifiers. Provides high gloss, easy application, and excellent durability. Responsive to high-speed burnishing.

Directions

For best results, use only after a complete strip and re-ocat. Floor should be rinsed and allowed to dry completely before refinishing.

Personal protective equipment:

Use eye and hand protection when using this product.

For floor finishing:

Use a clean finish mop or applicator to apply 2 - 5 coats of finish.
Allow 30 - 45 minutes of drying time between coats.
Allow 48 - 72 hours before replacing furniture or other heavy objects.

For daily maintenance:

- Sweep or dust mop floor daily, or more often for heavy traffic areas.
- 2 Damp mop at least daily using a neutral floor cleaner.

For restoration:

- **1** For low speed maintenance: Use a White or Beige Pad.
- **2** For high speed and propane burnishing: Use a Beige or other medium aggressive pad.





Applications

Floor finish for:

- > Hotels and motels
- > Hospitals and nursing homes
- > Offices and schools

Specifications

| Color | White |
|----------------------|----------------------|
| Fragrance | Characteristic |
| pH Range | 8.0 - 8.5 |
| Dilution | RTU |
| Density | 8.60 |
| Non-volatile solids. | 20% |
| Coverage | .2000 sq. ft. / gal. |

Packaging

5 gallon 956200-05

Product Certifications

Hard Floor Care Products UL 2777

