



Aluminum Bright Brightener and Cleaner

AUTOMOTIVE

DESCRIPTION

This product is designed to brighten aluminum and aluminum alloys. It is a balanced compound that penetrates and dissolves oxidized surface film, bringing out the natural luster of the metal. Excellent for continuous maintenance of aluminum and alloy highway trailers and mobile homes, stainless trailers, and aluminum building panels, maintaining an attractive, clean appearance. This product removes black soot.

APPLICATIONS

Use to remove road grime, film, and heavy dirt deposits on:

- Aluminum and Aluminum Alloys
- Stainless Trailers
- Highway Trailers

- Mobile Homes
- Aluminum Building Panels

FEATURES

- Concentrated
- Polishes
- Shines

DIRECTIONS

FOR NORMALLY SOILED ALUMINUM: Use 1-2 oz. of product per gallon of water.

FOR HEAVILY SOILED AND BADLY CORRODED ALUMINUM: Use 6-12 oz. of product per gallon of water.

FOR STAINLESS STEEL: Use 25 oz. of product per gallon of water on heavily soiled surface and 13 oz. per gallon of water on lightly soiled surface.

1. Whenever possible, place unit to be brightened in shaded area.
2. Wet entire surface with clear water. If surface is hot, use longer wetting procedure to cool surface.
3. Apply product with washing brush, low pressure sprayer, or, if high pressure washer is used, keep nozzle at least 18 inches from surface so brightener is applied lightly to accomplish wetting with a minimum amount of brightening solution.
4. Always start wetting with brightener from the bottom, wetting only as much surface as can be conveniently worked at one time (usually 10 - 5 linear feet). DO NOT ALLOW BRIGHTENER TO DRY ON SURFACE.
5. Keep the surface uniformly wetted with product for 3 - 5 minutes, depending on the amount of soil or corrosion, rewetting once or twice.

6. Rinse each section from bottom to top with plenty of clear water before going to the next section to be brightened. A pressure washer rinse at this point greatly speeds up the brightening procedure.

7. When entire trailer has been brightened, flush off top of trailer with clear water to prevent residual brightener on top from dripping and streaking. Then rinse down the sides again thoroughly with plenty of water to dilute and rinse away remaining brightener. In this rinse, a hose is better because the volume of water is important in this step. A hose delivers 5 - 9 g.p.m. as opposed to 2 g.p.m. from most pressure washers.

ATTENTION: Do not mix with bleach, chlorinated cleaners, ammoniated cleaners or alkaline compounds. The manufacturer warrants that this material conforms to the description on the label. The manufacturer neither makes nor authorizes any agent or representative to make any other warranty, expressed or implied, regarding the effectiveness, use or application of this product. The preceding applies whether or not specific recommendations were made or followed.

DO NOT HANDLE THIS PRODUCT WITHOUT WEARING NIOSH APPROVED EYE, SKIN AND RESPIRATORY PROTECTION.

SPECIFICATIONS

Color.....Colorless
Fragrance.....None
pH Range.....<1.0

Dilution 1-25 oz./gal.
Density 9.67

CW1198-414/1 gal.
CW1198-05..... 5 gal.

