

MAXIM PLUSTM

LABEL SYSTEM

Dry Bright Floor Finish

Features:

Economical

Hard, Durable, Non-Yellowing

Easy to Apply, with Good Off-the-Mop Gloss

Description

A very durable floor finish that reduces the need for strip and recoat due to its mix-metal cross link technology. Responds very well to occasional high speed burnishing or spray buffing.

Directions

-  **Wear safety glasses & gloves**
Usar gafas de seguridad y guantes
-  **Apply 3 - 5 coats evenly with clean finish mop**
Aplique uniformemente 3-5 capas con una mopa de acabado limpia
-  **Allow to dry 30 - 45 minutes between coats**
Deje secar 30-45 minutos entre una capa y otra
-  **Completely dry before applying next coat**
Seque completamente antes de aplicar la capa siguiente
-  **Let dry dry completely before allowing traffic**
Dejar secar completamente antes de permitir el tránsito



Applications

- For low maintenance areas in:**
- > Schools and hospitals
 - > Airports
 - > Offices

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.5 - 9.0
Dilution	RTU
Density	8.50
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	131600-41
5 gallon	131600-05
2/2.5 gallon	131600-07
55 gallon	131600-55