



Foam Up

Non-Butyl Foaming Degreaser

Espuma No Butilo Desengrasante

FOOD SERVICE

DESCRIPTION

This labor-saving product forms a thick, stable foam that clings to vertical surfaces when applied through a “foam gun” apparatus. A longer contact time will allow this product to easily remove grease, oil, fat, dirt, and grime from virtually all washable surfaces. Versatile and economical, this product is also an effective cleaner/degreaser when applied by more conventional means such as trigger sprayer, mop, or pressure sprayer.

APPLICATIONS

Ideal for:

- * Removing grease, dirt, and grime from virtually all washable surfaces

FEATURES

- * High Foaming Formula
- * Clings to Vertical Surfaces
- * Penetrates and Loosens Soils
- * Non-Butyl

DIRECTIONS

FOAMING APPLICATIONS: Dilution requirements will vary depending on the type of foaming device, water temperature, amount and type of soil, desired contact time, etc. For best results, experiment with different dilutions to determine which provides the most stable foam with your foaming equipment. For most devices, optimum foam production is at 2 oz. of product per gallon of water. Adjustments in product concentration may then be made based on cleaning requirements and desired product usage.

FOR NORMAL FOAMING AND CLEANING: Use 2 oz. of product per gallon of water.

FOR HEAVIER SOILS: Use up to 6 oz. of product per gallon of water. Apply foam liberally to all soiled surfaces and allow sufficient time for foam to penetrate, loosen, emulsify, and dissolve soils. Rinse thoroughly with potable water. Rinsing under high pressure dramatically enhances results.

OTHER APPLICATIONS: This versatile product may also be diluted and applied by trigger sprayer, mop, sponge, brush, etc.

SPECIFICATIONS

Color..... Red
Fragrance..... None
pH Range..... 12.5 - 13.0
Dilution 2 - 6 oz./gal.
Density 8.84

FS2450-414/1 gal.
FS2450-05 5 gal.
FS2450-5555 gal.

