

MAXIM PLUSTM

LABEL SYSTEM

Floor Sealer

Features:

Seals & Finishes Most Porous Stone, Terrazzo, & Concrete Floors
Extremely Durable & Economical

Description

This product is especially useful as a base coat on old, worn VCT, Linoleum, and asphalt tiles prior to application of floor finish. Its special wetting agents allow for the penetration and sealing of microscopic pores and ridges of non-resilient floor surfaces.

Directions

- 

1 **Wear safety glasses & gloves**
Usar gafas de seguridad y guantes
- 

2 **Apply 1 - 2 coats evenly with clean mop**
Aplique uniformemente 1-2 capas con una mopa de limpieza
- 

3 **Allow to dry 30 - 45 minutes between coats**
Deje secar 30-45 minutos entre una capa y otra
- 

4 **Completely dry before applying next coat**
Seque completamente antes de aplicar la capa siguiente
- 

5 **Apply floor finish**
Aplique el acabado para pisos



Applications

- For low maintenance areas such as:**
- > Schools and offices
 - > Hospitals and institutions
 - > Supermarkets and shopping centers

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.50
Coverage	2000 sq. ft. / gal.

Packaging

4/1 gallon	115000-41
5 gallon	115000-05
2/2.5 gallon	115000-07
55 gallon	115000-55