



# **Low Maintenance Floor Finish**

### **Features:**

Economical and Durable
Excellent Off-the-Mop Gloss
Easy to Maintain, Non-Yellowing

# **Description**

The ideal product for high traffic areas such as classrooms and entrance ways due the extended wear properties. This product is extremely durable. High hardness properties reduce maintenance by controlling scuffing and scratching. This product fits non-buff and spray buff programs. Ideal for use in areas where recoating time is limiting and maximum durability and gloss are desired.

## **Directions**



Wear safety glasses & gloves

Usar gafas de seguridad y guantes

2

**Apply 3 - 5 coats evenly with clean finish mop** *Aplique uniformemente 3-5 capas con una mopa de acabado limpia* 

3



**Allow to dry 30 - 45 minutes between coats**Deje secar 30-45 minutos entre una capa y otra

4



**Completely dry before applying next coat** Seque completamente antes de aplicar la capa siguiente

5



**Let dry completely before allowing traffic** *Dejar secar completamente antes de permitir el tránsito* 



### **Applications**

#### For low maintenance areas such as:

- > Schools
- > Hospitals
- > Offices

#### **Specifications**

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.55
Coverage	2000 sq. ft. / gal.

Packaging	
4/1 gallon	121800-41
5 gallon	121800-05
2.5 gallon	122500-07
55 gallon	121800-55



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY