



# **Ultra Durable Floor Finish**

### **Features:**

*High Solids - Requires Fewer Coats / Less Labor Durable, Non-Yellowing Excellent Off-the-Mop Gloss* 

## **Description**

Using a patented mixed metal cross-link technology Ultra Durable Floor Finish achieves superior lay down gloss in fewer coats and resists marks, scuffs, and scratching better than other premium low maintenance floor polishes. As few as two coats are needed for most applications. The finish dries to a clear film that will not yellow over time.

# **Directions**



Wear safety glasses & gloves Usar gafas de seguridad y guantes

**Apply 3 - 5 coats evenly with clean finish mop** *Aplique uniformemente 3-5 capas con una mopa de acabado limpia* 

Allow to dry 30 - 45 minutes between coats Deje secar 30-45 minutos entre una capa y otra

**Completely dry before applying next coat** *Seque completamente antes de aplicar la capa siguiente* 

**Let dry completely before allowing traffic** *Dejar secar completamente antes de permitir el tránsito* 



#### Applications

#### For regular stripping / buffing in:

- > Schools and hospitals
- > Airports
- > Offices

#### Specifications

Color	White
Fragrance	Characteristic
pH Range	
Dilution	RTU
Density	
Coverage	2000 sq. ft. / gal.

### Packaging

4/1 gallon	122500-41
2.5 gallon	122500-07
5 gallon	122500-05
55 gallon	122500-55



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 8P89



Contact your Account Representative for more information

**III LAD** 140 Private Brand Way, Athens, TN 37303 | 800.467.6294 | *fax:* 423.337.3369 | **midlab.com** erything Clean © 2018 Midlab, Inc. All right reserved. PLUS Label System is a trademark of Midlab, Inc.Patent Pending.